



SKYBOX SECURITY

APPLIANCE 7000

Enterprise networks demand continuous, high-end performance from their security appliance solutions. You need to get up and running fast with easy installation and keep up with evolving networks with little to no maintenance. You need Skybox® Appliance 7000.

- Total reliability and optimized performance
- Proven scalability in enterprise networks
- Easy installation

HIGHLIGHTED FEATURES

	SPECIFICATIONS
Processors	<ul style="list-style-type: none">• One Xeon E3-1270 v5 Processor, 3.6 GHz, 4 cores, total 8 threads
Power Supply	<ul style="list-style-type: none">• Two 450W redundant AC, hot swappable
Power Cables	<ul style="list-style-type: none">• IEC C13 to UK BS1363, IEC C13 to US NEMA 5-15P, and IEC C13 to EU CEE 7/7
RAM	<ul style="list-style-type: none">• 64GB DDR4 ECC DIMM (4x16GB)
Data Storage	<ul style="list-style-type: none">• RAID 1, 2x 2TB, 7200 RPM
Form Factor	<ul style="list-style-type: none">• One U rack
Size/Dimensions (HxWxD)	<ul style="list-style-type: none">• 1.70" x 17.25" x 23.84" (43.20 mm x 438.15 mm x 605.56 mm)
Weight	<ul style="list-style-type: none">• 19.6 lbs (8.87 kg)

	SPECIFICATIONS	
Compliance Standards	<p>Safety Compliance</p> <ul style="list-style-type: none"> • UL60950 — CSA 60950 (USA/Canada) • EN60950 (Europe) • IEC60950 (International) • CB Certificate and Report, IEC60950 (report to include all national deviations) • CE — Low Voltage Directive 2006/95/EC (Europe) 	<p>EMC Compliance — Class A</p> <ul style="list-style-type: none"> • FCC/ICES-003 — Emissions (USA/Canada) Verification • CISPR 22 — Emissions (International) and CISPR 24 — Immunity (International) • EN55022 — Emissions (Europe) • EN55024 — Immunity (Europe) • CE — EMC Directive 2004/108 EC (Europe) • AS/NZS 3548 Emissions (Australia/New Zealand) • BSMI CNS13438 Emissions (Taiwan) • KC Certification (Korea)
System Cooling	<ul style="list-style-type: none"> • Three managed 40 mm single rotor system fans • Two power supply fans 	
Heat Output	<ul style="list-style-type: none"> • 840.7 BTU/hour 	
Operating Environment	<p>Operating Temperature</p> <ul style="list-style-type: none"> • ASHRAE Class A2: Continuous operation, 10° C to 35° C (50° F to 95° F) with maximum rate of change not to exceed 10° C per hour • ASHRAE Class A3: Includes operation up to 40° C (104° F) for up to 900 hours per year <p>Shipping Temperature</p> <ul style="list-style-type: none"> • -40° C to 70° C (-40° F to 158° F) <p>Non-Operating Humidity</p> <ul style="list-style-type: none"> • 50 percent to 90 percent, non-condensing with a maximum wet bulb of 28° C (at temperatures from 25° C to 35° C / 75° F to 95° F) 	

ABOUT SKYBOX SECURITY

At Skybox, we remove complexities from cybersecurity management. By integrating data, delivering new insights and unifying processes, we help you control security without restricting business agility. Our comprehensive solution unites security perspectives into the big picture, minimizes risk and empowers security programs to move to the next level.